

ViewSonic® VA902 LCD Monitor

19" A SERIES LCD DISPLAY



Ultra-fast with attractive styling.

The 19" ViewSonic VA902 combines an attractive silver and black design with the innovative ViewSonic **CLEARMOTIV™** 8ms video response with **VIBRANT, CLEAR IMAGES**. It is designed to enhance your work and play but only have minimal impact on your wallet. This **ULTRA-SLIM BEZEL LCD DELIVERS AN IMPRESSIVE ARRAY OF FEATURES**. The AutoTune function automatically optimises screen images and the OSD lock and power button lock functions prevent accidental changes to screen settings while the fold-up base makes wall mounting a snap. This stylish LCD is a perfect choice for your home office.

Stylish, speedy, affordable

→ ClearMotiv™ 8ms video response time

8ms video response enables digital broadcast-quality full-motion video.

→ Stylish slim-bezel design

An ultra-thin bezel lets you see more without taking up valuable desktop real estate.

→ Ultra-high brightness and contrast

270 cd/m² brightness (typ.) and 550:1 contrast ratio (typ.) for rich, detailed images.

→ Full 19" viewable

→ 1280 x 1024 resolution

→ OSD/power lock secures your settings

Prevents changes to monitor settings and maintains an optimized image.

→ OnView® controls for superior screen adjustability

Screen adjustments are precisely made via an easy-to-use on-screen menu.

→ sRGB colour management

For a closer match of image display to print outs.

→ ViewSonic Wizard included

User-friendly Wizard software automates the setup process to deliver optimized screen performance.

→ Flat-folding base for easy wall mounting (VESA® 100mm)

→ Integrated power supply

→ PC and Mac® compatible

→ Kensington® security slot

→ TCO'03 and ENERGY qualified

ViewSonic® 
the choice of professionals

Clear Choice

ViewSonic® VA902 LCD Monitor

19" A SERIES LCD DISPLAY



1. One-touch buttons control all major functions
2. Slim bezel with a 90-degree fold-up base
3. Space-saving design is only 6.1cm thick
4. Ultra compact, attractive design



Available colours:
Black/Silver dual tone

19" LCD DISPLAY WITH 8MS CLEARMOTIV™ BROADCAST QUALITY

LCD	Type	19" TN-Colour TFT Active Matrix SXGA LCD
	Display Area	376mm horizontal x 301mm vertical; 48.3cm diagonal
	Pixel Pitch	0.294mm
	Optimum Resolution	1280 x 1024
	Pixel Clock	135MHz
	Contrast Ratio	550:1 (typ.)
	Viewing Angle	140° horizontal, 135° vertical @ 10:1 160° horizontal, 160° vertical @ 5:1
	Response Time	8ms (typ.)
	Colour Support	16.2M colours (6-bit + 2-bit FRC)
	Brightness	270cd/m² (typ.)
	Panel Surface	Anti-glare 3H
INPUT SIGNAL	Video	RGB analogue (75 ohms, 0.7 Vp-p)
	Sync	H/V separated (TTL)
	Frequency	Fh: 30-82kHz, Fv: 50-85Hz
COMPATIBILITY	PC	VGA up to 1280 x 1024 (@ max. 75Hz non-interlaced)
	Mac[®]1	Power Mac™ G3/G4/G5 1152 x 870 (@ max. 75Hz)
CONNECTOR	Analogue	15-pin mini D-Sub (attached cable)
	Power	3-pin AC plug, (CEE22)
POWER	Voltage	AC 100-240V, 50-60Hz (auto switch), internal power supply
	Consumption	35W (typ.)
ERGONOMICS	Tilt	Down 5°, Up 20°
CONTROLS	Physical	Power on/off, menu, down, up, select
	OSD	Auto image adjust, brightness, contrast, ViewMatch® colour adjust [sRGB, 9300K, 6500K (default), 5400K, user colour (R,G,B)], information [resolution, H. frequency, V. frequency, pixel clock, model number, serial number], manual image adjust [H. size, H./V. position, fine tune, sharpness, scaling], setup menu [language (English, French, German, Italian, Spanish, Finnish, Japanese, Traditional Chinese, Simplified Chinese), resolution notice, OSD position, OSD timeout, OSD background], memory recall, OSD lock, power lock
OPERATING CONDITIONS	Temperature	0°C to 40°C
	Humidity	10% to 90% (non-condensation)
DIMENSIONS	(W x H x D mm)	414 x 407 x 219
WEIGHT	Net	5.4kg
REGULATIONS		TCO'03, CE, CB, TÜV/GS, TÜV/ERGO, ISO13406-2 (pixel fault class II), UL, cUL, FCC-B, ENERGY, EPA Energy Star, NOM, GOST-R, (SASO), ICES 003, BSMI, CCC, PSB, (C-TICK), TÜV-S
POWER MANAGEMENT		Meets TCO'03, Energy and EPA Energy Star standards
PACKAGE-CONTENTS		LCD display, power cable, 15-pin VGA video cable, Quick Start Guide, ViewSonic Wizard CD
WARRANTY		Please see: www.viewsoniceurope.com/UK/Support/warranty.htm



ViewSonic Corporation's QMS/EMS has been registered to ISO 9001 & ISO 14001 by the British Standards Institution.

ViewSonic 
the choice of professionals

ViewSonic Europe Limited/UK
ViewSonic House
Fleming Way, Crawley
West Sussex, RH10 9GA
United Kingdom

Tel: +44 (0) 12 93 64 39 00
Fax: +44 (0) 12 93 64 39 10

ViewSonic Germany
Hanns-Martin-Schleyer-Straße 18A
47877 Willlich
Germany

Tel: +49 (0) 21 54 91 88 0
Fax: +49 (0) 21 54 91 88 10

ViewSonic France
Parc des Barbannières
1 allée des Bas Tilliers
92230 Gennevilliers
France

Tel: +33 (0) 1 41 47 49 00
Fax: +33 (0) 1 41 47 49 10

ViewSonic Corporation
381 Brea Canyon Road
Walnut
California 91789-0708
USA

Tel: +1 909 869 7976
Fax: +1 909 869 7958

ViewSonic Benelux
ViewSonic Denmark
ViewSonic Finland
ViewSonic Italy
ViewSonic MEA
ViewSonic Norway
ViewSonic Spain
ViewSonic Sweden

Tel: +32 056/85 26 27
Tel: +45 70 22 11 71
Tel: +358 (9) 54 06 40 70
Tel: +39 02 5832 0356
Tel: +971 (0) 4 88 11 871
Tel: +47 (0) 22 88 17 60
Tel: +34 (0) 91 63 05 339
Tel: +46 (0) 8 50 71 30 00

¹May require optional Mac adapter

Copyright © 2005, ViewSonic Corporation. All rights reserved. Specifications subject to change without notice. Corporate names and trademarks stated herein are the property of their respective companies. VS VA902-05/05-UK

For more information, visit us on the web at www.ViewSonicEurope.com